



Old world craftsmanship ... today's technology®

CAST Lighting LED's Specifications Summary

Model #	Name	Light Source	Voltage Range (V)	Color Temp (CCT) (°K)	Color Rendering Index (CRI)	Lamp Life (L70) (Hrs.)	Wattage @12v AC (Watts) (High/Low)	Power Factor @12v	Ap-parent Power (VA) @12V (High/Low)	Light Output (LED Array) (Lm) (High/Low)	Light Output (from fixture) (Lm) (High/Low)	Center Beam Candle-power (CBCP) (cd)				
Security (Perimeter) Lights																
CPL1	CAST LED Perimeter Light	(3) Cree XTE with integrated driver in replaceable module	12-24 AC/DC	4,450	77	36,300	7.0	0.82	8.5	512	265	-				
CPWP1	CAST LED Perimeter Wall Pack										490	-				
Stake/Talon/Canopy Mount Directional, Wash & Specialty Lights																
CID140 & CIDA140	CAST Impressionist LED Directional Light (40°)	(1) Cree XML with dimmer, integrated driver, replaceable module	10-24 AC/DC	2,800	84	42,300	5.0	0.72	6.9	299	253	450				
CIT164	CAST Impressionist LED Tree Light (64°)										242	222				
CIWL6	CAST Impressionist LED Wall Wash Light										(2) Cree XML with dimmer, integrated driver, replaceable module	8.5	0.88	9.7	530	352
CBLED141	CAST LED MR-16 Bullet (41°)	(3) Cree XPG with integrated driver in replaceable module	9.6 - 28.8 AC/DC	2,800	84	60,500	10.0/6.7	0.92	10.9/7.3	391/290	391/290	-				
CTLED141	CAST LED Tree Light (41°)										6.6/4.5	0.92	7.2/4.9	333/253	333/253	-
CWW1LED2	CAST LED Wall Wash	(2) Cree XPE with integrated driver in replaceable module	10 - 24 AC/DC	2,800	84	60,500	4.4	0.85	5.2	270	270	-				
CWL6LED1	CAST LED Mini Wash (Stake Mount)	(2) Cree XTE with integrated driver in replaceable module									5.3	0.9	5.9	150 Avg.	50	
CEWL56) LED1	CAST LED Engineered Wall Light	(1) Cree XPE with integrated driver in replaceable module									3.0	0.8	3.8	105	75	25
CDL1LED1	CAST LED Deck Light	(1) Cree XPE with integrated driver in replaceable module									3.0	0.8	3.8	120	60	35
Path / Area Lights (For Path Lights with CAST LED Modules, see next section)																
CCH5LED1	CAST LED Mini China Hat Area/Path	Dynasty 1156 (replaceable)	8.0-25.0 AC/DC	2,800	85	35,000	1.5	0.8	1.9	100	100	-				
CSA1LED2	CAST LED Savannah Area/Path Light	(2) Cree XPE with integrated driver in replaceable module	10 - 24 AC/DC		84	60,500	4.4	0.85	5.2	270	270	-				
LED Path Light Modules																
CALED2	CAST LED Path Light Module	(2) Cree XPE with integrated driver in replaceable module	10 - 24 AC/DC	2,800	84	60,500	4.4	0.85	5.2	270	160 Avg.	-				
CSWLED2	CAST LED Path Light Module for CSA1CB & CWW1CB										270	-				
Turtle-Safe Lights (Meets standards set by Florida Fish and Wildlife Conservation Commission)																
CWW1LED2A	CAST LED Wall Wash - Amber	(2) Cree XPE with integrated driver in replaceable module	10 - 24 AC/DC	NA	NA	50,000	3.9	0.85	4.6	130	130	-				
CSA1LED2A	CAST LED Savannah Area/Path Light - Amber										130	-				
CDL1LED1A	CAST Turtle-Safe Amber LED Deck Light	(1) Cree XPE Amber with integrated driver in replaceable module	10 - 24 AC/DC	NA	NA	50,000	2.7	0.83	3.3	70	35	-				

Specifications subject to change without notice. ©Copyright 2013, CAST Lighting LLC.